

Gamma 2




PRODUCT DESCRIPTION


The GAMMA 2 LED bollard range blends style with functionality, offering an impressive output of up to 1500 lumens and an efficiency of up to 88 LI/cW. Designed with a robust extruded aluminum housing and equipped with vandal-resistant screws, it includes an internal driver tray for straightforward maintenance and comes complete with a mounting kit and 200mm anchor bolts. Available with either a flat or domed top, each bollard is finished in a black powdercoat (RAL9005) over a durable chromate conversion coating. Its optical system features a reflective white polycarbonate cone reflector paired with a clear, vandal-resistant polycarbonate lens for optimal light distribution.

A stainless steel version of the domed model is also offered, constructed from 316 marine-grade stainless steel for outstanding corrosion resistance, making it ideal for coastal or industrial environments. This sturdy, recyclable option is not only highly resistant to wear and vandalism but also enhances any outdoor setting with its sleek, contemporary look. Its resilient design provides long-lasting performance with minimal upkeep, making it a sustainable and secure choice for lighting paths, service roads, and open spaces.

FEATURES



DIMENSIONS



mm	735	736
H	1073	1057
W	178	178
KG	6.5	6.2

PRODUCT DATA

GAMMA 2				
Product code	Curcuit Watts (w)	Delivered Lumens	Colour Temp	Efficacy LI/cW
Dome				
735.1500.840	16	1550	4000	94
Flat				
736.1500.840	16	1500	4000	94

PRODUCT OPTIONS



* Stainless Steel option only available on the 735 Domed Top only.

LED PERFORMANCE

25° Ambient Temperature	L70/B50
GAMMA 2	100,000

'L' Value = % of Initial Lumens maintained after specified time
'B' Value = % of fittings failing to meet operational expectations after specified time

PHOTOMETRIC PERFORMANCE

