

SOLA



XXX.X.XXX.C



XXX.X.XXX.SN

LED
87 LI/cW
 L70 25,000
 84

PRODUCT DESCRIPTION

The SOLA fire rated downlight range sets new levels in performance. Featuring a sparkling low glare multifaceted lens with an efficacy of up to 87 LI/cW and 640 delivered lumens overall. An integrated driver and sprung side arms ensure optimum performance with energy saving LED technology and simple cost effective installation. Available with either fixed or adjustable beam direction and a removable bezel in three colours with white as standard. Fixed version bezel is IP65 as standard. Adjustable version bezel is IP20 as standard.

FEATURES

- Ingress Protection Adjustable version only
- Ingress Protection Fixed version only
- Colour Temperature 4000k
- Fire Rated

DIMENSIONS

	(mm)	301	302	305	306
HD		60	70	68	75
D		78	85	70	97
H		75	93	93	98
KG		0.22	0.28	0.26	0.37

PRODUCT DATA

SOLA				
Product code	Circuit Watts (w)	Delivered Lumens	Efficacy LI/cW	Fixed/Adj
301.5.380	5	380	84	Fixed
302.8.620	8	620	74	Fixed
305.5.390	5	390	87	Adjustable
306.8.640	8	640	78	Adjustable

PRODUCT OPTIONS

Correlated colour temp 3000k XXX.X.XXX.3K

3 hr Emergency XXX.X.XXX.EM3

Chrome XXX.X.XXX.C


Satin Nickel XXX.X.XXX.SN

LED PERFORMANCE

25° Ambient Temperature	L70/B50
SOLA	25,000

'L' Value = % of initial Lumens maintained after specified time
'B' Value = % of fittings failing to meet operational expectations after specified time

PHOTOMETRIC PERFORMANCE



- SOLA
- Output - 640
- Watts - 8
- LOR - 100%
- SHR MAX = 1:1