

STAR



Brass xxx.xxx.**BR**



Chrome xxx.xxx.**C**



Silver xxx.xxx.**S**



Black xxx.xxx.**B**



PRODUCT DESCRIPTION

The STAR LED is a single or double sided suspended exit sign luminaire utilising high quality LEDs to provide energy savings and extended life expectancy. A versatile design allows the sign to be wall mounted, ceiling mounted or semi recessed.


Robustly fabricated mild steel construction is finished in white epoxy powder coat as standard with a variety of alternative colour finishes available.

Suitable for corridors, final exits and escape routes in retail and commercial applications.

FEATURES

- IP20** Ingress Protection
- 4000k** Colour Temperature
- 24m** Legend Viewing Distance

DIMENSIONS







| | (mm) |
|-------------------|------|
| L | 310 |
| W | 40 |
| H (Surface) | 260 |
| H (Semi Recessed) | 265 |
| KG | 2.0 |

PRODUCT DATA

| STAR | | | | |
|--------------|---------------|-------------|-------------------|------------------|
| Product code | Application | Colour Temp | Circuit Watts (w) | Delivered Lumens |
| 850.125 | Surface | 4000 | 3 | 150 |
| 855.125 | Semi Recessed | 4000 | 3 | 150 |

PRODUCT OPTIONS



LEGENDS

| | | | | | |
|--|-----------------------------|-------------|--|-----------------------------------|-------------|
| | Down Single Sided | 85X.125.LG1 | | Right Single Sided | 85X.125.LG2 |
| | Left Single Sided | 85X.125.LG3 | | Final Exit Single Sided | 85X.125.LG4 |
| | Double Sided Down | 85X.125.LG5 | | Double Sided Left/Right | 85X.125.LG6 |

LED PERFORMANCE

| | |
|--------------------------------|----------------|
| 25° Ambient Temperature | L70/B50 |
| STAR | 36,000 |

¹ 'L' Value = % of initial Lumens maintained after specified time
² 'B' Value = % of fittings failing to meet operational expectations after specified time